

| CLEAR SPAN | LOAD TYPE | (U) LBS./SF (C) LBS./FT & RESULTING DEFLECTION IN INCHES | | | | | | | | | | | | | | SAFE LD FCTR 2:1 | DEFL |
|------------|-----------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------------------|-------|
| | | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 750 | 1000 | 2000 | 2500 | 3000 | 4000 | | |
| 12" | U | 0.001 | 0.002 | 0.003 | 0.004 | 0.006 | 0.007 | 0.009 | 0.011 | 0.017 | 0.022 | 0.044 | 0.055 | 0.066 | 0.088 | 10075 | 0.223 |
| | C | 0.002 | 0.004 | 0.005 | 0.007 | 0.009 | 0.011 | 0.014 | 0.018 | 0.027 | 0.035 | 0.071 | 0.088 | 0.106 | 0.142 | 5038 | 0.178 |
| 18" | U | 0.005 | 0.010 | 0.015 | 0.020 | 0.026 | 0.031 | 0.041 | 0.051 | 0.077 | 0.102 | 0.204 | 0.255 | 0.306 | 0.408 | 4477 | 0.457 |
| | C | 0.005 | 0.011 | 0.016 | 0.022 | 0.027 | 0.033 | 0.044 | 0.054 | 0.082 | 0.109 | 0.218 | 0.272 | 0.326 | -- | 3358 | 0.365 |
| 24" | U | 0.015 | 0.030 | 0.046 | 0.061 | 0.076 | 0.091 | 0.122 | 0.152 | 0.228 | 0.305 | 0.609 | -- | -- | -- | 2519 | 0.767 |
| | C | 0.012 | 0.024 | 0.037 | 0.049 | 0.061 | 0.073 | 0.097 | 0.122 | 0.183 | 0.244 | 0.487 | 0.609 | -- | -- | 2519 | 0.614 |
| 30" | U | 0.035 | 0.071 | 0.106 | 0.141 | 0.177 | 0.212 | 0.283 | 0.353 | 0.53 | -- | -- | -- | -- | -- | 1597 | 1.128 |
| | C | 0.023 | 0.045 | 0.068 | 0.090 | 0.113 | 0.136 | 0.181 | 0.226 | 0.339 | 0.452 | -- | -- | -- | -- | 1996 | 0.903 |
| 36" | U | 0.071 | 0.142 | 0.213 | 0.284 | 0.356 | 0.427 | 0.569 | -- | -- | -- | -- | -- | -- | -- | 1092 | 1.553 |
| | C | 0.038 | 0.076 | 0.114 | 0.152 | 0.190 | 0.228 | 0.303 | 0.379 | 0.569 | -- | -- | -- | -- | -- | 1638 | 1.242 |
| 42" | U | 0.127 | 0.253 | 0.380 | 0.506 | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | 786 | 1.989 |
| | C | 0.058 | 0.116 | 0.174 | 0.231 | 0.289 | 0.347 | 0.463 | 0.578 | -- | -- | -- | -- | -- | -- | 1375 | 1.591 |
| 48" | U | 0.212 | 0.424 | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | 590 | 2.499 |
| | C | 0.085 | 0.170 | 0.254 | 0.339 | 0.424 | 0.509 | -- | -- | -- | -- | -- | -- | -- | -- | 1179 | 1.999 |

U - Uniform Load - Lbs./Sf. C - Concentrated Load - Lbs./Ft. of Width at Mid Span | Loading information based on 5.66 bearing bars per foot of Grating width. Product weighs 2.50 Lbs./Sf. Safe load values have a safety factor of 2:1 (two to one). Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Fiberglass Grating.

 ADA compliant spacing (1/2" maximum clear opening) when the direction of bearing bars (span) are installed perpendicular to the dominant direction of travel.