STANDARD PRODUCT & SHEARING TOLERANCES



CHART

SERIES NAME	CONSTRUCTION TYPE	SURFACE PROFILE	SQUARENESS TOLERANCE			SHEARING TOLERANCE	
			WIDTH	LENGTH	DIAGONAL	WIDTH	LENGTH
DIAMONDBACK®	EXTRUDED INTERLOCKING FLOORING	SOLID, DIAMOND-VENTED					+/- 1/8"
SAFDECK®	OVERLAPPING DECKING	SOLID, SLOTTED	+/- 1/4"	+/- 1/4"	+/- 1/4"		+/- 1/4"
SAFPLANK®	INTERLOCKING PLANK FLOORING	SOLID, SLOTTED	+/- 1/4"	+/- 1/4"	+/- 1/4"		+/- 1/4"
SAFPLATE®	FIBERGLASS FLOORING	SOLID	+/- 1/4"	+/- 1/4"	+/- 1/4"	+/- 1/4"	+/- 1/4"
TRACTION TREAD™	METAL FLOORING	BUTTON-TOP				+/- 1/8"	+/- 1/8"

Due to the differences in primary material types (e.g. Aluminum, Stainless Steel, etc.), some tolerances may vary slightly from those listed above. Technical information provided is for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. McNICHOLS shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Decking or Flooring.