


HEIGHT (mm)	LBS./LF (kg/m) SOLID	LOAD/ DEFL	CLEAR SPAN										
			12"	18"	24"	30"	36"	42"	48"	54"	60"	66"	72"
0.360" (9.14)	1.966 (2.93)	<b>U</b>	390	173	97	62	42	31	23	18	15	12	10
		<b>D</b>	0.107	0.241	0.428	0.669	0.963	1.311	1.712	2.166	2.675	3.236	3.851
		<b>C</b>	195	130	97	77	64	54	47	41	39	33	30
		<b>D</b>	0.197	0.664	1.574	3.075	5.314	8.438	12.596	17.934	24.601	32.743	42.510

**U** - Uniform Load - Lbs. per Square Foot

**D** - Deflection - in Inches

**C** - Concentrated Load - Lbs. per Square Foot of Width at Mid Span

- Loading values are based on the solid version of the product.
  - Loading and deflection values are theoretical and based on a tensile bending stress of 19,000 PSI.
  - Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk.
- McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Extruded Interlocking Flooring.
-  ADA compliant product.

