FIBERGLASS GRATING STAIR TREAD PANEL & COVER

MS-T-R-150 RECTANGULAR GRID | MS-T-COVER WITH 2" RADIUS LIP

MOLDED LOAD TABLE

SERIES TYPE	GRID	TREAD COVER	GRID SIZE	TREAD COVER	COMMON	MAXIMUM TREAD SPAN (300 LBS. AT MID SPAN)	
& NAME	HEIGHT	THICKNESS	& SHAPE	SURFACE	WIDTHS	1/8" DEFLECTION OR LESS	1/4" DEFLECTION OR LESS
MS-T-R-150	1-1/2"		1-1/2" x 6" RECTANGULAR GRID		7-5/8"; 9-1/8"; 10-5/8"	31"	38"
MS-T-COVER		1/8"		SOLID WITH 2" RADIUS LIP	8"; 9"; 10"; 11"; 12"	31"	38"

- Stair Tread Panels are supplied in gray and green with a grit surface and integral nosing on both sides (length) of the Panel. They are produced with a 22-1/2" width and 120" length and may be cut to desired width and length (span).
- Stair Tread Cover Panels are supplied in black with yellow 2" radius lip and a grit surface. They are produced in various widths (9" and 10" in stock) and 144" in length and may be cut to desired width and length (span).
- Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Tread Panel and Stair Tread Cover Panel.

