

SERIES TYPE & NAME	BEARING BAR SHAPE	BEARING BAR HEIGHT & TOP FLANGE WIDTH	WIDTH (inches)	MAXIMUM TREAD SPAN (300 LBS. AT MID SPAN)	
				1/8" DEFLECTION OR LESS	1/4" DEFLECTION OR LESS
MS-I-ST-6010 - DURAGRID®	I-BAR	1.000" x 0.600"	11"	29"	37"
MS-I-ST-6015 - DURAGRID®	I-BAR	1.500" x 0.600"	11"	40"	52"
MS-T-ST-5020 - DURAGRID®	T-BAR	2.000" x 1.000"	12"	47"	59"

- Stair Tread Panels come in yellow and light gray with a medium grit surface and a 2" wide integral nosing on one side of the Panel length.
- Stair Tread I-Bar Panels are produced with an 11" width and 144" length and may be cut to desired width and length (span).
- Stair Tread T-Bar Panels are produced with a 12" width and 144" length and may be cut to desired width and length (span).
- Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Tread Panel.

