



SERIES TYPE & NAME	BEARING BAR SHAPE	BEARING BAR HEIGHT & TOP FLANGE WIDTH	TREAD PANEL WIDTH	MAXIMUM TREAD SPAN (300 LBS. AT MID SPAN)	
				1/8" DEFLECTION OR LESS	1/4" DEFLECTION OR LESS
MS-I-ST-6010 - DURAGRID®	I-BAR	1.000" x 0.600"	11"	29"	37"
MS-I-ST-6015 - DURAGRID®	I-BAR	1.500" x 0.600"	11"	40"	52"
MS-T-ST-5020 - DURAGRID®	T-BAR	2.000" x 1.000"	12"	47"	59"

Stair Tread Panels come in yellow and light gray with a medium grit surface and 2" wide integral nosing on one side of the panel's length. Stair Tread I-Bar Panels are produced with an 11" width and 144" length and may be cut to desired width and length (span). Stair Tread T-Bar Panels are produced with a 12" width and 144" length and may be cut to desired width and length (span). Technical information provided is for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. McNICHOLS® shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Fiberglass Grating Stair Tread Panels.

