

GAUGE	DEPTH (mm)	LBS./LF (kg/m)	LOAD/ DEFL	CLEAR SPAN																
				24"	30"	36"	42"	48"	54"	60"	66"	72"	78"	84"	90"	96"	108"	120"	132"	144"
11	2" (50.8)	8.50 (12.6)	U	1624	1039	721	530	405	320	259	214	182	153	132	115	102	80	66	54	45
			D	0.05	0.08	0.11	0.15	0.19	0.24	0.30	0.35	0.41	0.47	0.54	0.62	0.69	0.85	1.04	1.24	1.45
			C	1860	1488	1244	1063	930	827	744	677	620	572	531	496	465	413	372	338	310
			D	0.04	0.06	0.09	0.12	0.15	0.19	0.24	0.28	0.33	0.38	0.44	0.49	0.55	0.68	0.81	0.98	1.16
	2-1/2" (63.5)	8.90 (13.2)	U	2460	1615	1093	804	615	485	393	325	214	233	201	175	153	122	99	83	68
			D	0.05	0.07	0.10	0.14	0.18	0.23	0.27	0.32	0.36	0.42	0.49	0.55	0.62	0.79	0.96	1.15	1.35
			C	2820	2256	1880	1611	1410	1254	1128	1025	940	868	806	752	705	626	564	513	470
	3" (76.2)	9.30 (13.8)	U	2618	1676	1164	855	655	516	419	347	290	248	214	186	163	130	104	87	73
			D	0.04	0.06	0.08	0.11	0.15	0.18	0.22	0.26	0.30	0.34	0.39	0.44	0.48	0.58	0.68	0.80	0.95
			C	3000	2400	2000	1715	1500	1333	1180	1091	1000	923	857	800	750	667	600	545	500
10	4" (101.6)	10.1 (15.0)	U	4293	2748	1909	1402	1075	849	689	568	476	408	351	306	268	212	172	141	118
			D	0.03	0.05	0.07	0.09	0.12	0.14	0.17	0.20	0.23	0.27	0.31	0.35	0.39	0.47	0.56	0.66	0.78
			C	4920	3936	3280	2812	2460	2187	1968	1789	1640	1514	1406	1312	1230	1094	935	895	820
			D	0.03	0.04	0.06	0.07	0.09	0.11	0.14	0.16	0.19	0.22	0.25	0.31	0.38	0.45	0.53	0.63	
	2" (50.8)	9.50 (14.1)	U	1804	1154	801	589	450	356	288	238	202	170	147	128	113	89	73	60	50
			D	0.05	0.08	0.11	0.15	0.19	0.24	0.30	0.35	0.41	0.47	0.54	0.62	0.69	0.85	1.04	1.24	1.45
			C	2067	1653	1378	1181	1033	919	827	752	689	636	590	551	517	459	413	316	344
	2-1/2" (63.5)	10.0 (14.9)	U	2733	1794	1214	893	683	539	437	361	304	259	223	194	170	136	110	92	76
			D	0.04	0.06	0.09	0.12	0.15	0.19	0.24	0.28	0.33	0.38	0.44	0.49	0.55	0.68	0.81	0.98	1.16
			C	3133	2507	2089	1790	1567	1393	1253	1139	1044	964	895	836	783	696	627	570	522
9	3" (76.2)	10.5 (15.6)	U	2909	1862	1293	950	728	513	466	385	322	275	238	207	181	144	115	97	81
			D	0.04	0.06	0.08	0.11	0.15	0.18	0.22	0.26	0.30	0.34	0.39	0.44	0.48	0.58	0.68	0.80	0.95
			C	3333	2667	2222	1905	1667	1481	1311	1212	1111	1026	952	889	833	741	667	606	556
	4" (101.6)	11.4 (16.9)	U	4770	3053	2121	1558	1194	943	765	631	529	453	390	340	298	236	191	157	131
			D	0.03	0.05	0.07	0.09	0.12	0.14	0.17	0.21	0.24	0.28	0.31	0.35	0.39	0.47	0.55	0.64	0.76
			C	5467	4373	3644	3124	2733	2430	2187	1988	1822	1682	1562	1458	1367	1215	1039	994	911
			D	0.03	0.04	0.06	0.07	0.09	0.11	0.14	0.16	0.19	0.22	0.25	0.31	0.38	0.46	0.53	0.63	

U - Uniform Load - Lbs./Sf. D - Deflection in Inches C - Concentrated Load - Lbs./Ft. of Width at Mid Span | Span and loading values to the left of the bolded black line produce a deflection of 1/4" or less under a uniform load of 100 Lbs./Sf., allowing for safe pedestrian comfort. Span and loading values to the right of the bolded black line are applicable to other types of loads at the discretion of a licensed engineer. Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Plank Grating.