

GAUGE	WIDTH (mm)	DEPTH (mm)	#/LF (kg/m)	LOAD	CLEAR SPAN			
					24"	30"	36"	42"
10	9-1/4" (35.0)	2" (50.8)	7.4 (11.0)	U	2412	1544	1026	629
				C	1860	1487	1240	929

U - Uniform Load - Lbs. per Square Foot

C - Concentrated Load - Lbs. per Square Foot of Width at Mid Span

- For Stair Treads with lengths (spans) greater than 48", an intermediate stringer is recommended.
- Loading values in table are based on a Stair Tread with a 9-1/4" Width and a 2" Depth. A 13-3/4" Width, 2" Depth Stair Tread size is also available.
- Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Treads.

STAIR TREAD & CARRIER PLATE DIMENSIONS					STAIR TREAD & CARRIER PLATE END VIEW
WIDTH (mm)	Ⓐ (mm)	Ⓑ (mm)	Ⓒ (mm)	Ⓓ (mm)	
9-1/4" (235.0)	2" (50.8)	9-1/4" (235.0)	1" (25.4)	5-7/8" (149.2)	
<p>Ⓐ Channel Depth of Stair Tread</p> <p>Ⓑ Width of Stair Tread</p> <p>Ⓒ Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Hole to Flat Surface of Stair Tread</p> <p>Ⓓ Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Hole</p>					

