

SURFACE PROFILE	WIDTH (mm)	DEPTH (mm)	PRIMARY MATERIAL	GAUGE/ THICK	#/LF (kg/m)	LOAD	CLEAR SPAN	
							48-3/4"	60"
2-ROW	1-1/4" (31.8)	1-1/2" (38.1)	ALUMINUM	0.1250"	0.56 (0.83)	<b>C</b>	207	187
			CARBON & GALV. STEEL	13	1.18 (1.76)	<b>C</b>	328	252
				11	1.52 (2.26)	<b>C</b>	515	383
			STAINLESS STEEL	16	0.82 (1.22)	<b>C</b>	218	183
3-ROW	1-5/8" (41.3)	1-1/8" (28.6)	ALUMINUM	0.1250"	0.50 (0.74)	<b>C</b>	163	135
			CARBON & GALV. STEEL	13	1.06 (1.58)	<b>C</b>	187	151
				11	1.46 (2.17)	<b>C</b>	297	229
			STAINLESS STEEL	16	0.73 (1.09)	<b>C</b>	151	103
4-ROW	2-1/4" (57.2)	1-1/2" (38.1)	ALUMINUM	0.1250"	0.70 (1.04)	<b>C</b>	280	248
			CARBON & GALV. STEEL	13	1.49 (2.22)	<b>C</b>	372	274
				11	2.08 (3.10)	<b>C</b>	523	408
			STAINLESS STEEL	16	1.03 (1.53)	<b>C</b>	236	201

**C** - Concentrated Load - Lbs. per Square Foot of Width at Mid Span

- Safe load values have a minimum safety factor of 2.0.
- Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Ladder Rung Plank.

