

THICK	DEPTH (mm)	LBS./LF (kg/m)	LOAD/ DEFL	CLEAR SPAN												
				24"	30"	36"	42"	48"	54"	60"	66"	72"	78"	84"	90"	96"
.0800"	1-1/2" (38.1)	1.06 (1.58)	U	667	443	301	221	168	133	108	--	--	--	--	--	--
			D	0.10	0.15	0.22	0.31	0.40	0.51	0.63	--	--	--	--	--	--
			C	395	316	263	226	197	175	157	--	--	--	--	--	--
			D	0.08	0.12	0.18	0.25	0.32	0.41	0.50	--	--	--	--	--	--
	2" (50.8)	1.15 (1.71)	U	993	636	441	324	248	196	159	131	110	93	80	--	--
			D	0.08	0.13	0.18	0.25	0.33	0.42	0.52	0.63	0.74	0.86	1.00	--	--
			C	579	463	386	331	290	257	232	211	192	177	165	--	--
			D	0.06	0.10	0.15	0.20	0.27	0.34	0.42	0.51	0.59	0.69	0.80	--	--
	2-1/2" (63.5)	1.24 (1.85)	U	1492	955	663	487	373	295	2391	197	166	141	122	106	93
			D	0.07	0.10	0.15	0.21	0.28	0.35	0.43	0.53	0.63	0.74	0.85	0.98	1.12
			C	812	696	580	491	435	387	348	316	290	268	249	232	218
			D	0.05	0.08	0.12	0.17	0.22	0.28	0.35	0.42	0.50	0.59	0.68	0.78	0.89
	3" (76.2)	1.33 (1.98)	U	1833	1173	815	598	458	362	293	2421	204	174	150	130	115
			D	0.06	0.09	0.14	0.19	0.25	0.31	0.39	0.47	0.56	0.66	0.77	0.88	1.00
			C	846	846	713	611	535	475	428	389	356	329	305	285	267
			D	0.03	0.07	0.11	0.15	0.20	0.25	0.31	0.38	0.45	0.53	0.61	0.70	0.80
.1000"	1-1/2" (38.1)	1.34 (1.99)	U	771	494	343	252	193	152	122	101	--	--	--	--	--
			D	0.09	0.15	0.22	0.30	0.39	0.50	0.63	0.76	--	--	--	--	--
			C	450	360	300	251	225	200	179	162	--	--	--	--	--
			D	0.07	0.12	0.17	0.24	0.31	0.40	0.51	0.61	--	--	--	--	--
	2" (50.8)	1.46 (2.17)	U	1391	890	618	454	348	275	223	184	155	132	114	99	87
			D	0.09	0.14	0.20	0.28	0.37	0.46	0.58	0.70	0.83	0.98	1.13	1.30	1.48
			C	811	649	541	464	406	361	325	295	270	250	232	216	203
			D	0.07	0.11	0.16	0.22	0.29	0.37	0.46	0.56	0.66	0.78	0.90	1.04	1.18
	2-1/2" (63.5)	1.57 (2.34)	U	1913	1225	850	625	478	378	306	253	213	181	156	136	120
			D	0.07	0.11	0.16	0.22	0.28	0.36	0.45	0.54	0.64	0.76	0.88	1.01	1.15
			C	1116	893	744	638	558	496	446	406	372	343	319	298	279
			D	0.05	0.09	0.12	0.11	0.23	0.29	0.36	0.43	0.51	0.60	0.70	0.81	0.92
	3" (76.2)	1.68 (2.50)	U	2470	1581	1098	807	618	488	395	327	274	234	202	176	154
			D	0.05	0.08	0.12	0.17	0.22	0.28	0.34	0.42	0.50	0.59	0.68	0.78	0.89
			C	1309	1153	961	823	720	640	576	524	480	443	412	384	360
			D	0.04	0.06	0.10	0.13	0.17	0.22	0.27	0.33	0.40	0.47	0.54	0.62	0.71

U - Uniform Load - Lbs./Sf. **D** - Deflection in Inches **C** - Concentrated Load - Lbs./Ft. of Width at Mid Span | Span and loading values to the left of the bolded black line produce a deflection of 1/4" or less under a uniform load of 100 Lbs./Sf., allowing for safe pedestrian comfort. Span and loading values to the right of the bolded black line are applicable to other types of loads at the discretion of a licensed engineer. Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Plank Grating.