

| PROFILE<br>(width) | GAUGE | DEPTH<br>(mm) | LBS./LF<br>(kg/m) | LOAD/<br>DEFL | CLEAR SPAN |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|--------------------|-------|---------------|-------------------|---------------|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|                    |       |               |                   |               | 24"        | 30"  | 36"  | 42"  | 48"  | 54"  | 60"  | 66"  | 72"  | 78"  | 84"  | 90"  | 96"  | 108" | 120" | 132" | 144" |
| 13-HOLE<br>(24")   | 11    | 2"<br>(50.8)  | 8.9<br>(13.2)     | U             | 1094       | 700  | 486  | 357  | 273  | 216  | 175  | 145  | 123  | 105  | 91   | 79   | 70   | 56   | 45   | 38   | 33   |
|                    |       |               |                   | D             | 0.03       | 0.05 | 0.06 | 0.09 | 0.12 | 0.15 | 0.18 | 0.22 | 0.26 | 0.31 | 0.36 | 0.41 | 0.47 | 0.60 | 0.75 | 0.92 | 1.13 |
|                    |       | 3"<br>(76.2)  | 9.8<br>(14.5)     | C             | 2092       | 1674 | 1395 | 1196 | 1046 | 930  | 837  | 761  | 697  | 644  | 598  | 558  | 540  | 504  | 459  | 423  | 393  |
|                    |       |               |                   | D             | 0.02       | 0.03 | 0.05 | 0.06 | 0.09 | 0.11 | 0.14 | 0.17 | 0.20 | 0.23 | 0.27 | 0.31 | 0.37 | 0.49 | 0.61 | 0.74 | 0.90 |
|                    | 11    | 2"<br>(50.8)  | 11.8<br>(17.5)    | U             | 1971       | 1261 | 876  | 644  | 493  | 389  | 315  | 261  | 219  | 187  | 161  | 141  | 124  | 99   | 80   | 67   | 57   |
|                    |       |               |                   | D             | 0.02       | 0.03 | 0.04 | 0.06 | 0.08 | 0.10 | 0.12 | 0.15 | 0.18 | 0.21 | 0.24 | 0.28 | 0.32 | 0.40 | 0.50 | 0.61 | 0.73 |
|                    |       | 3"<br>(76.2)  | 12.7<br>(18.5)    | C             | 3792       | 3033 | 2528 | 2167 | 1896 | 1685 | 1517 | 1379 | 1264 | 1167 | 1083 | 1011 | 948  | 843  | 758  | 689  | 632  |
|                    |       |               |                   | D             | 0.01       | 0.02 | 0.03 | 0.04 | 0.05 | 0.07 | 0.09 | 0.10 | 0.12 | 0.15 | 0.17 | 0.19 | 0.22 | 0.30 | 0.38 | 0.46 | 0.54 |
| 16-HOLE<br>(30")   | 11    | 2"<br>(50.8)  | 11.8<br>(17.5)    | U             | 956        | 612  | 425  | 312  | 239  | 189  | 153  | 126  | 106  | 91   | 77   | 68   | 60   | 47   | 38   | 32   | 27   |
|                    |       |               |                   | D             | 0.02       | 0.03 | 0.04 | 0.05 | 0.07 | 0.09 | 0.11 | 0.13 | 0.16 | 0.18 | 0.21 | 0.24 | 0.28 | 0.35 | 0.43 | 0.52 | 0.62 |
|                    |       | 3"<br>(76.2)  | 12.7<br>(18.5)    | C             | 2564       | 2051 | 1709 | 1465 | 1282 | 1140 | 1026 | 932  | 855  | 789  | 733  | 684  | 641  | 570  | 513  | 466  | 421  |
|                    |       |               |                   | D             | 0.01       | 0.02 | 0.03 | 0.04 | 0.06 | 0.07 | 0.09 | 0.10 | 0.12 | 0.15 | 0.17 | 0.20 | 0.22 | 0.28 | 0.35 | 0.42 | 0.50 |
|                    | 11    | 3"<br>(76.2)  | 12.7<br>(18.5)    | U             | 1413       | 904  | 628  | 461  | 353  | 279  | 226  | 187  | 157  | 134  | 116  | 100  | 89   | 70   | 57   | 46   | 39   |
|                    |       |               |                   | D             | 0.02       | 0.03 | 0.04 | 0.06 | 0.08 | 0.10 | 0.12 | 0.14 | 0.17 | 0.20 | 0.23 | 0.26 | 0.30 | 0.38 | 0.47 | 0.57 | 0.67 |
|                    |       | 4"<br>(101.6) | 13.5<br>(20.1)    | C             | 3802       | 3041 | 2534 | 2172 | 1901 | 1690 | 1521 | 1382 | 1267 | 1170 | 1086 | 1014 | 950  | 845  | 760  | 691  | 634  |
|                    |       |               |                   | D             | 0.01       | 0.02 | 0.03 | 0.04 | 0.05 | 0.01 | 0.09 | 0.10 | 0.12 | 0.14 | 0.17 | 0.19 | 0.22 | 0.28 | 0.34 | 0.41 | 0.53 |

**U** - Uniform Load - Lbs./Sf. **D** - Deflection in Inches **C** - Concentrated Load - Lbs./Ft. of Width at Mid Span | Span and loading values to the left of the bolded black line produce a deflection of 1/4" or less under a uniform load of 100 Lbs./Sf., allowing for safe pedestrian comfort. Span and loading values to the right of the bolded black line are applicable to other types of loads at the discretion of a licensed engineer. Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Plank Grating.