

| PRIM MATL | GAUGE/ THICK | DEPTH (mm) | LBS./LF (kg/m) | LOAD/ DEFL | CLEAR SPAN | | | | | | | | | | | | | | | | | |
|---------------------------|-----------------|------------------|-------------------|---------------|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|--|
| | | | | | 24" | 30" | 36" | 42" | 48" | 54" | 60" | 66" | 72" | 78" | 84" | 90" | 96" | 108" | 120" | 132" | 144" | |
| ALUMINUM | .1250" | 2" (50.8) | 1.50 (2.20) | U | 2138 | 1491 | 1035 | 761 | 582 | 460 | 372 | 308 | 258 | 221 | 190 | 166 | 146 | 115 | 93 | 77 | 65 | |
| | | | | D | 0.07 | 0.14 | 0.20 | 0.27 | 0.35 | 0.44 | 0.54 | 0.66 | 0.78 | 0.92 | 1.07 | 1.23 | 1.39 | 1.76 | 2.18 | 2.64 | 3.14 | |
| | | | | C | 1509 | 1207 | 1006 | 862 | 755 | 611 | 604 | 549 | 503 | 464 | 431 | 402 | 377 | 335 | 302 | 274 | 252 | |
| | | | | D | 0.07 | 0.11 | 0.16 | 0.21 | 0.28 | 0.35 | 0.44 | 0.53 | 0.63 | 0.74 | 0.85 | 0.98 | 1.12 | 1.41 | 1.74 | 2.11 | 2.51 | |
| CARBON & GALVANIZED STEEL | 13 | 1-1/2" (38.1) | 3.00 (4.40) | U | 1536 | 984 | 685 | 504 | 387 | 306 | 249 | 206 | 174 | 149 | 129 | 112 | 100 | 79 | 65 | 55 | 46 | |
| | | | | D | 0.05 | 0.01 | 0.11 | 0.14 | 0.19 | 0.24 | 0.29 | 0.36 | 0.43 | 0.50 | 0.58 | 0.67 | 0.77 | 0.98 | 1.22 | 1.51 | 1.81 | |
| | | 2" (50.8) | 3.30 (4.90) | C | 914 | 731 | 609 | 522 | 457 | 406 | 366 | 332 | 305 | 283 | 263 | 246 | 232 | 208 | 190 | 174 | 162 | |
| | | | | D | 0.04 | 0.06 | 0.08 | 0.12 | 0.15 | 0.19 | 0.24 | 0.29 | 0.34 | 0.40 | 0.47 | 0.54 | 0.61 | 0.78 | 0.98 | 1.20 | 1.44 | |
| | 11 | 1-1/2" (38.1) | 4.20 (6.20) | U | 1981 | 1269 | 883 | 650 | 498 | 394 | 320 | 265 | 224 | 191 | 165 | 144 | 128 | 101 | 83 | 69 | 59 | |
| | | | | D | 0.05 | 0.07 | 0.11 | 0.15 | 0.19 | 0.24 | 0.30 | 0.36 | 0.43 | 0.51 | 0.59 | 0.68 | 0.18 | 0.98 | 1.22 | 1.50 | 1.81 | |
| | | 2" (50.8) | 4.50 (6.70) | C | 1165 | 932 | 777 | 666 | 582 | 518 | 467 | 426 | 391 | 362 | 337 | 316 | 297 | 266 | 241 | 222 | 205 | |
| | | | | D | 0.04 | 0.06 | 0.09 | 0.12 | 0.15 | 0.19 | 0.24 | 0.29 | 0.34 | 0.40 | 0.47 | 0.54 | 0.62 | 0.79 | 0.98 | 1.20 | 1.44 | |
| STAINLESS STEEL | 16 | 3" (76.2) | 4.80 (7.10) | U | 2899 | 1978 | 1375 | 1012 | 776 | 614 | 498 | 411 | 347 | 302 | 261 | 228 | 201 | 160 | 130 | 108 | 92 | |
| | | | | D | 0.03 | 0.06 | 0.08 | 0.11 | 0.15 | 0.19 | 0.23 | 0.28 | 0.34 | 0.40 | 0.47 | 0.54 | 0.62 | 0.78 | 0.97 | 1.18 | 1.42 | |
| | | 2" (50.8) | 2.40 (3.60) | C | 1762 | 1410 | 1175 | 1032 | 904 | 805 | 726 | 661 | 607 | 573 | 533 | 499 | 469 | 420 | 380 | 348 | 321 | |
| | | | | D | 0.03 | 0.05 | 0.07 | 0.09 | 0.12 | 0.15 | 0.19 | 0.23 | 0.27 | 0.32 | 0.37 | 0.43 | 0.49 | 0.63 | 0.78 | 0.95 | 1.14 | |
| | 16 | 2" (50.8) | 2.40 (3.60) | U | 5806 | 3716 | 2581 | 1898 | 1454 | 1150 | 932 | 771 | 649 | 554 | 479 | 417 | 367 | 291 | 236 | 196 | 166 | |
| | | | | D | 0.03 | 0.04 | 0.06 | 0.08 | 0.11 | 0.13 | 0.17 | 0.20 | 0.24 | 0.28 | 0.33 | 0.37 | 0.43 | 0.54 | 0.67 | 0.81 | 0.98 | |
| | | 3" (76.2) | 4.80 (7.10) | C | 3188 | 2550 | 2125 | 1822 | 1594 | 1417 | 1275 | 1159 | 1132 | 1050 | 976 | 913 | 857 | 764 | 690 | 630 | 581 | |
| | | | | D | 0.02 | 0.03 | 0.04 | 0.06 | 0.07 | 0.10 | 0.12 | 0.15 | 0.19 | 0.22 | 0.26 | 0.30 | 0.34 | 0.43 | 0.54 | 0.65 | 0.78 | |

U - Uniform Load - Lbs./Sf. **D** - Deflection in Inches **C** - Concentrated Load - Lbs./Ft. of Width at Mid Span | Span and loading values to the left of the bolded black line produce a deflection of 1/4" or less under a uniform load of 100 Lbs./Sf., allowing for safe pedestrian comfort. Span and loading values to the right of the bolded black line are applicable to other types of loads at the discretion of a licensed engineer. Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Plank Grating.