

SERIES TYPE & NAME	BB HGT	BB THK	LBS./SF		LOAD/DEFL	CLEAR SPAN																		
			15-P-4	15-P-2		12"	18"	24"	30"	36"	42"	48"	54"	60"	66"	72"	78"	84"	90"	96"	102"	108"	114"	120"
GCC-75-A & GDD-75-A	3/4"	1/8"	1.7	2.0	U	1200	533	300	192	133	98	75	59	48	40	33	28	24	21	19	17	15	13	12
					D	0.048	0.108	0.192	0.300	0.431	0.588	0.767	0.967	1.199	1.463	1.709	1.997	2.303	2.655	3.110	3.546	3.933	4.232	4.796
					C	600	400	300	240	200	171	150	133	120	109	100	92	86	80	75	71	67	63	60
					D	0.038	0.086	0.153	0.240	0.345	0.469	0.614	0.775	0.959	1.160	1.381	1.616	1.886	2.158	2.455	2.788	3.123	3.454	3.837
GCC-75 & GDD-75	3/4"	3/16"	2.5	2.7	U	1800	800	450	288	200	147	113	89	72	60	50	43	37	32	28	25	22	20	18
					D	0.048	0.108	0.192	0.300	0.432	0.588	0.771	0.973	1.200	1.464	1.727	2.046	2.368	2.699	3.057	3.479	3.848	4.343	4.799
					C	900	600	450	360	300	257	225	200	180	164	150	138	129	120	113	106	100	95	90
					D	0.038	0.086	0.154	0.240	0.345	0.470	0.614	0.777	0.960	1.164	1.382	1.617	1.887	2.159	2.468	2.777	3.109	3.474	3.839
GCC-100-A & GDD-100-A	1"	1/8"	2.3	2.6	U	2134	948	533	341	237	174	133	105	85	71	59	50	44	38	33	30	26	24	21
					D	0.036	0.081	0.144	0.225	0.324	0.441	0.575	0.727	0.897	1.097	1.291	1.507	1.783	2.029	2.282	2.643	2.879	3.300	3.545
					C	1067	711	533	427	356	305	267	237	213	194	178	164	152	142	133	126	119	112	107
					D	0.029	0.065	0.115	0.180	0.260	0.353	0.461	0.583	0.719	0.872	1.038	1.216	1.408	1.618	1.839	2.090	2.343	2.593	2.890
GCC-100 & GDD-100	1"	3/16"	3.3	3.5	U	3200	1422	800	512	356	261	200	158	128	106	89	76	65	57	50	44	40	35	32
					D	0.036	0.081	0.144	0.225	0.324	0.441	0.576	0.729	0.900	1.091	1.298	1.526	1.756	2.029	2.304	2.584	2.952	3.207	3.600
					C	1600	1067	800	640	533	457	400	356	320	291	267	246	229	213	200	188	178	168	160
					D	0.029	0.065	0.115	0.180	0.259	0.353	0.461	0.584	0.720	0.871	1.038	1.216	1.414	1.617	1.843	2.078	2.336	2.593	2.880
GCC-125-A & GDD-125-A	1-1/4"	1/8"	2.8	3.1	U	3334	1482	833	533	370	272	208	165	133	110	93	79	68	59	52	46	41	37	33
					D	0.029	0.065	0.115	0.180	0.259	0.353	0.460	0.585	0.718	0.870	1.041	1.218	1.411	1.613	1.840	2.075	2.324	2.604	2.851
					C	1667	1111	833	667	556	476	417	370	333	303	278	256	238	222	208	196	185	175	167
					D	0.023	0.052	0.092	0.144	0.208	0.282	0.369	0.466	0.575	0.697	0.830	0.972	1.129	1.295	1.472	1.664	1.864	2.074	2.309
GCC-125 & GDD-125	1-1/4"	3/16"	4.0	4.3	U	5000	2222	1250	800	556	408	313	247	200	165	139	118	102	89	78	69	62	55	50
					D	0.029	0.065	0.115	0.180	0.259	0.353	0.462	0.583	0.720	0.870	1.038	1.213	1.411	1.622	1.840	2.075	2.343	2.581	2.880
					C	2500	1667	1250	1000	833	714	625	556	500	455	417	385	357	333	313	294	278	263	250
					D	0.023	0.052	0.092	0.144	0.207	0.282	0.369	0.467	0.576	0.698	0.830	0.974	1.129	1.295	1.477	1.664	1.868	2.078	2.304
GCC-150-A & GDD-150-A	1-1/2"	1/8"	3.4	3.8	U	4800	2133	1200	768	533	392	300	237	192	159	133	114	98	85	75	66	59	53	48
					D	0.024	0.054	0.096	0.150	0.216	0.294	0.384	0.486	0.600	0.727	0.862	1.017	1.176	1.345	1.536	1.723	1.935	2.158	2.400
					C	2400	1600	1200	960	800	686	600	533	480	436	400	369	343	320	300	282	267	253	240
					D	0.019	0.043	0.077	0.120	0.173	0.235	0.307	0.389	0.480	0.580	0.691	0.811	0.941	1.080	1.229	1.385	1.557	1.735	1.920
GCC-150 & GDD-150	1-1/2"	3/16"	4.8	5.2	U	7200	3200	1800	1152	800	588	450	356	288	238	200	170	147	128	113	100	89	80	72
					D	0.024	0.054	0.096	0.150	0.216	0.294	0.384	0.487	0.600	0.726	0.864	1.012	1.176	1.350	1.543	1.740	1.946	2.172	2.400
					C	3600	2400	1800	1440	1200	1029	900	800	720	655	600	554	514	480	450	424	400	379	360
					D	0.019	0.043	0.077	0.120	0.173	0.235	0.307	0.389	0.480	0.581	0.691	0.811	0.940	1.080	1.229	1.389	1.555	1.733	1.920
GCC-175 & GDD-175	1-3/4"	3/16"	5.6	5.9	U	9800	4356	2450	1568	1089	800	613	484	392	324	272	232	200	174	153	136	121	109	98
					D	0.021	0.046	0.082	0.129	0.185	0.252	0.329	0.417	0.514	0.622	0.740	0.869	1.008	1.156	1.315	1.490	1.666	1.864	2.057
					C	4900	3267	2450	1960	1633	1400	1225	1089	980	891	817	754	700	653	613	576	544	516	490
					D	0.016	0.037	0.066	0.103	0.148	0.202	0.263	0.333	0.411	0.498	0.593	0.695	0.806	0.925	1.054	1.188	1.332	1.486	1.646
GCC-200 & GDD-200	2"	3/16"	6.3	6.7	U	12800	5689	3200	2048	1422	1045	800	632	512	423	356	303	261	228	200	177	158	142	128
					D	0.018	0.041	0.072	0.113	0.162	0.221	0.288	0.364	0.450	0.544	0.649	0.761	0.881	1.014	1.152	1.299	1.458	1.626	1.800
					C	6400	4267	3200	2560	2133	1829	1600	1422	1280	1164	1067	985	914	853	800	753	711	674	640
					D	0.014	0.032	0.058	0.090	0.130	0.176	0.230	0.292	0.360	0.436	0.519	0.609	0.705	0.810	0.922	1.040	1.166	1.300	1.440
GCC-225 & GDD-225	2-1/4"	3/16"	7.0	7.4	U	16200	7200	4050	2592	1800	1322	1013	800	648	536	450	383	331	288	253	224	200	180	162
					D	0.016	0.036	0.064	0.100	0.144	0.196	0.256	0.324	0.400	0.484	0.576	0.675	0.785	0.900	1.024	1.155	1.296	1.448	1.600
					C	8100	5400	4050	3240	2700	2314	2025	1800	1620	1473	1350	1246	1157	1080	1013	953	900	853	810
					D	0.013	0.029	0.051	0.080	0.115	0.157	0.205	0.259	0.320	0.387	0.461	0.541	0.627	0.720	0.820	0.925	1.037	1.156	1.280
GCC-250 & GDD-250	2-1/2"	3/16"	7.8	8.1	U	20000	8889	5000	3200	2222	1633	1250	988	800	661	556	473	408	356	313	277	247	222	200
					D	0.014	0.032	0.058	0.090	0.130	0.176	0.230	0.292	0.360	0.435	0.519	0.608	0.705	0.811	0.923	1.041	1.167	1.302	1.440
					C	10000	6667	5000	4000	3333	2857	2500	2222	2000	1818	1667	1538	1429	1333	1250	1176	1111	1053	1000
					D	0.012	0.026	0.046	0.072	0.104	0.141	0.184	0.233	0.288	0.348	0.415	0.487	0.565	0.648	0.737	0.832	0.933	1.040	1.152

U - Uniform Load - Lbs. per Square Foot

D - Deflection - in Inches

C - Concentrated Load - Lbs. per Square Foot of Width at Mid Span

- Span and loading values to the left of the bolded black line produce a deflection of 1/4" or less under a uniform load of 100 lbs. per square foot, allowing for safe pedestrian comfort. Span and loading values to the right of the bolded black line are applicable to other types of loads at the discretion of a licensed engineer.
- GCC and GDD Series Grating is not designed for wheel traffic. GDD Series Grating refers to 2" cross bar spacing (15-P-2).
- Custom Order Only: For Grating with a serrated surface (1" bearing bar height or taller and 3/16" thick), subtract 1/4" from the bearing bar height requirement and reference that loading information listed in the table. For example, a 1-1/2" x 3/16" serrated bearing bar height and thickness would have the same strength and loading values as a 1-1/4" x 3/16" smooth (non-serrated) bearing bar height and thickness.
- Loading and deflection values are theoretical and based on a maximum allowable fiber stress (F_s) of 12,000 PSI, E = 10,000,000 PSI.
- Technical information provided is theoretical and for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. McNICHOLS shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Bar Grating.

Superior Service, Quality and Performance ... That's The Hole Story®!

