

STAIR TREADS (STANDARD) & CARRIER PLATES DIMENSIONS					STAIR TREAD (STANDARD) & CARRIER PLATE END VIEW
WIDTH (mm)	A (mm)	B (mm)	C (mm)	D (mm)	
4-3/4" (120.7)	1-1/2" (38.1)	4-3/4" (120.7)	3/4" (19.0)	2-5/8" (66.7)	
	2" (50.8)	4-3/4" (120.7)	1" (25.4)	2-5/8" (66.7)	
7" (177.8)	1-1/2" (38.1)	7" (177.8)	3/4" (19.0)	3-3/8" (85.7)	
	2" (50.8)	7" (177.8)	1" (25.4)	3-3/8" (85.7)	
9-1/2" (241.3)	1-1/2" (38.1)	9-1/2" (241.3)	3/4" (19.0)	5-7/8" (149.2)	
	2" (50.8)	9-1/2" (241.3)	1" (25.4)	5-7/8" (149.2)	
11-3/4" (298.5)	1-1/2" (38.1)	11-3/4" (298.5)	3/4" (19.0)	8-1/8" (206.4)	
	2" (50.8)	11-3/4" (298.5)	1" (25.4)	8-1/8" (206.4)	

- A Channel Depth of Stair Tread
- B Width of Stair Tread (Standard)
- C Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Hole to Flat Surface of Stair Tread
- D Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Hole

STAIR TREADS (WITH CAST ABRASIVE NOSING) & CARRIER PLATE DIMENSIONS					STAIR TREAD (WITH CAST ABRASIVE NOSING) & CARRIER PLATE END VIEW
WIDTH (mm)	A (mm)	B (mm)	C (mm)	D (mm)	
8-1/8" (206.4)	1-1/2" (38.1)	8-1/8" (206.4)	3/4" (19.0)	4-1/2" (114.3)	
	2" (50.8)	8-1/8" (206.4)	1" (25.4)	4-1/2" (114.3)	
10-1/2" (266.7)	1-1/2" (38.1)	10-1/2" (266.7)	3/4" (19.0)	6-7/8" (174.6)	
	2" (50.8)	10-1/2" (266.7)	1" (25.4)	6-7/8" (174.6)	

- A Channel Depth of Stair Tread
- B Width of Stair Tread (with Cast Abrasive Nosing)
- C Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Hole to Flat Surface of Stair Tread
- D Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Hole

- Charts apply to Aluminum, Carbon Steel, Galvanized Steel and Stainless Steel.
- Stainless Steel is not available in 2-Diamond or 3-Diamond widths.
- Technical information provided is for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. McNICHOLS shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Treads and Carrier Plates.

