

PRIMARY MATERIAL	GAUGE/ THICK (in)	DEPTH (mm)	SPAN (inches)	STAIR TREADS (STANDARD)		STAIR TREADS (WITH NOSING)		
				PROFILE	WIDTH	PROFILE	WIDTH	
ALUMINUM	.0800"	2" (50.8)	UP TO 42"	2-DIAMOND	4-3/4"	--	--	
				3-DIAMOND	7"	3-DIAMOND	8-1/8"	
				4-DIAMOND	9-1/2"	4-DIAMOND	10-1/2"	
				5-DIAMOND	11-3/4"	--	--	
	.1000"	2" (50.8)	UP TO 48"	2-DIAMOND	4-3/4"	--	--	
				3-DIAMOND	7"	3-DIAMOND	8-1/8"	
				4-DIAMOND	9-1/2"	4-DIAMOND	10-1/2"	
				5-DIAMOND	11-3/4"	--	--	
CARBON & GALVANIZED	14	1-1/2" (38.1)	UP TO 30"	2-DIAMOND	4-3/4"	--	--	
				3-DIAMOND	7"	3-DIAMOND	8-1/8"	
				4-DIAMOND	9-1/2"	4-DIAMOND	10-1/2"	
				5-DIAMOND	11-3/4"	--	--	
		1-1/2" (38.1)	30" TO 36"	2-DIAMOND	4-3/4"	--	--	
				3-DIAMOND	7"	3-DIAMOND	8-1/8"	
				4-DIAMOND	9-1/2"	4-DIAMOND	10-1/2"	
		1-1/2" (38.1)	36" TO 42"	2-DIAMOND	4-3/4"	--	--	
				3-DIAMOND	7"	3-DIAMOND	8-1/8"	
				4-DIAMOND	9-1/2"	4-DIAMOND	10-1/2"	
		2" (50.8)	UP TO 42"	5-DIAMOND	11-3/4"	--	--	
				2-DIAMOND	4-3/4"	--	--	
	3-DIAMOND			7"	3-DIAMOND	8-1/8"		
	4-DIAMOND			9-1/2"	4-DIAMOND	10-1/2"		
	STAINLESS STEEL TYPE 304	16	2" (50.8)	UP TO 30"	5-DIAMOND	11-3/4"	--	--
					4-DIAMOND	9-1/2"	--	--
STAINLESS STEEL TYPE 316L	16	2" (50.8)	UP TO 30"	4-DIAMOND	9-1/2"	--	--	
				5-DIAMOND	11-3/4"	--	--	

- Standard Stair Tread sizes and spans are based on approximately a minimum concentrated load of 300 lbs. and a minimum uniform load of 100 lbs.
- Technical information provided is theoretical and for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Treads.

