

STAIR TREADS & CARRIER PLATE DIMENSIONS					STAIR TREAD & CARRIER PLATE END VIEW
WIDTH (mm)	Ⓐ (mm)	Ⓑ (mm)	Ⓒ (mm)	Ⓓ (mm)	
5" (127.0)	1-1/2" (38.1)	4-15/16" (125.0)	3/4" (19.0)	2" (50.8)	
	2" (50.8)	4-15/16" (125.0)	1" (25.4)	2" (50.8)	
7" (177.8)	1-1/2" (38.1)	6-15/16" (176.0)	3/4" (19.0)	4" (101.6)	
	2" (50.8)	6-15/16" (176.0)	1" (25.4)	4" (101.6)	
10" (254.0)	1-1/2" (38.1)	9-15/16" (254.0)	3/4" (19.0)	7" (177.8)	
	2" (50.8)	9-15/16" (254.0)	1" (25.4)	7" (177.8)	
12" (304.8)	1-1/2" (38.1)	11-15/16" (303.0)	3/4" (19.0)	9" (228.6)	
	2" (50.8)	11-15/16" (303.0)	1" (25.4)	9" (228.6)	

- Carrier Plates are designed to be used with Stair Treads up to and including 48" in length (span).
- For Stair Treads with length (spans) greater than 48", an intermediate stringer is recommended.
- Technical information provided is for evaluation by technically skilled persons only, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Stair Tread and Carrier Plates.

- Ⓐ Channel Depth of Stair Tread
- Ⓑ Width of Stair Tread
- Ⓒ Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Hole to Flat Surface of Stair Tread
- Ⓓ Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Hole

