

STAIR TREADS & CARRIER PLATES DIMENSIONS							STAIR TREAD & CARRIER PLATE END VIEW
SURFACE PROFILE	WIDTH (mm)	CARRIER PLATES	Ⓐ (mm)	Ⓑ (mm)	Ⓒ (mm)	Ⓓ (mm)	
2-DIAMOND	4-3/4" (120.7)	CP-PG-215	1-1/2" (38.1)	4-3/4" (120.7)	3/4" (19.0)	2-5/8" (66.7)	
		CP-PG-220	2" (50.8)	4-3/4" (120.7)	1" (25.4)	2-5/8" (66.7)	
3-DIAMOND	7" (177.8)	CP-PG-315	1-1/2" (38.1)	7" (177.8)	3/4" (19.0)	3-3/8" (85.7)	
		CP-PG-320	2" (50.8)	7" (177.8)	1" (25.4)	3-3/8" (85.7)	
4-DIAMOND	9-1/2" (241.3)	CP-PG-415	1-1/2" (38.1)	9-1/2" (241.3)	3/4" (19.0)	5-7/8" (149.2)	
		CP-PG-420	2" (50.8)	9-1/2" (241.3)	1" (25.4)	5-7/8" (149.2)	
5-DIAMOND	11-3/4" (298.5)	CP-PG-515	1-1/2" (38.1)	11-3/4" (298.5)	3/4" (19.0)	8-1/8" (206.4)	
		CP-PG-520	2" (50.8)	11-3/4" (298.5)	1" (25.4)	8-1/8" (206.4)	

- Ⓐ Channel Depth of Stair Tread
- Ⓑ Width of Stair Tread
- Ⓒ Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Bolt Hole to Flat Surface of Stair Tread
- Ⓓ Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Bolt Hole

STAIR TREAD PLANKS (WITH NOSING) & CARRIER PLATE DIMENSIONS							STAIR TREAD PLANK (WITH NOSING) & CARRIER PLATE END VIEW
SURFACE PROFILE	WIDTH (mm)	CARRIER PLATES	Ⓐ (mm)	Ⓑ (mm)	Ⓒ (mm)	Ⓓ (mm)	
3-DIAMOND W/ NOSING SHELF	8-1/8" (206.4)	CP-PG-315-N	1-1/2" (38.1)	8-1/8" (206.4)	3/4" (19.0)	4-1/2" (114.3)	
		CP-PG-320-N	2" (50.8)	8-1/8" (206.4)	1" (25.4)	4-1/2" (114.3)	
4-DIAMOND W/ NOSING SHELF	10-1/2" (266.7)	CP-PG-415	1-1/2" (38.1)	10-1/2" (266.7)	3/4" (19.0)	6-7/8" (174.6)	
		CP-PG-420-N	2" (50.8)	10-1/2" (266.7)	1" (25.4)	6-7/8" (174.6)	

- Stair Treads without nosing shelf available in Aluminum: .0800" thick (12 gauge) and .1000" thick (10 gauge), Carbon Steel: 14 gauge (.0747" thick) and 12 gauge (.1046" thick), Galvanized Steel: 14 gauge (.0785" thick) and 12 gauge (.1084" thick) and Stainless Steel: 16 gauge (.0625" thick).
- Stair Tread Planks with nosing shelf available in Aluminum: .0800" thick (12 gauge) and .1000" thick (10 gauge), Carbon Steel: 14 gauge (.0747" thick) and 12 gauge (.1046" thick) and Galvanized Steel: 14 gauge (.0785" thick) and 12 gauge (.1084" thick).
- GRIP STRUT® Stair Tread Plank items have a 1-1/4" wide flat shelf to accept 1-1/4" wide Cast Abrasive Nosing.
- Technical information provided is for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. **McNICHOLS** shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Plank Grating Stair Treads, Stair Tread Planks and related Accessories/Components..

- Ⓐ Channel Depth of Stair Tread Plank
- Ⓑ Width of Stair Tread Plank (with 1-1/4" Wide Cast Abrasive 90° Angle Nosing)
- Ⓒ Center of 1-3/4" x 7/16" Slot and Center of 7/16" Diameter Bolt Hole to Flat Surface of Stair Tread
- Ⓓ Center of 1-3/4" x 7/16" Slot to Center of 7/16" Diameter Bolt Hole

