

TOLERANCE	WIDTH	LESS THAN 3/16" THICK		3/16" TO 3/8" THICK	
SHEARING	ALL WIDTHS	+/- 1/16"		+/- 1/8"	
TOLERANCE	GAUGE/ THICKNESS	UP TO 72"		UP TO 120"	
		MAX OUT OF SQUARE	DIAGONAL MEASURE DIFF	MAX OUT OF SQUARE	DIAGONAL MEASURE DIFF
RESQUARING	26 - 20 GAUGE	1/16"	1/8"	1/16"	1/8"
	19 - 16 GAUGE	1/16"	1/8"	1/8"	1/4"
	15 - 11 GAUGE	3/32"	3/16"	3/16"	3/8"
	10 GAUGE - 3/8" THICK	EDGES SHALL BE SUCH THAT ANY INTERSECTING SIDE SHALL NOT BE OUT OF SQUARE IN EXCESS OF 1/8" PER FOOT IN EITHER DIRECTION TO A MAXIMUM OF 1/2" OVERALL			
TOLERANCE	DIAMETER OF CIRCLE	26 GAUGE TO 12 GAUGE		11 GAUGE	
CIRCLES	3" - 48"	+/- 1/8"		+/- 3/16"	

For information on McNICHOLS® Perforated Metal flatness tolerances, please refer to the Perforated Metal Flatness Tolerance Chart. Technical information provided is for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. McNICHOLS shall have no responsibility or liability for results obtained or damages resulting from improper evaluation or use of Perforated Metal.