

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
1" x 1" MESH			
.250"	.7500"	56.3%	412.4
.225"	.7750"	60.1%	332.1
.207"	.7930"	62.9%	280.1
.192"	.8080"	65.3%	240.3
.177"	.8230"	67.7%	203.7
.162"	.8380"	70.2%	170.2
.148"	.8520"	72.6%	141.7
.135"	.8650"	74.8%	117.7
.120"	.8800"	77.4%	92.8
.105"	.8950"	80.1%	71.0
.092"	.9080"	82.4%	54.4
.080"	.9200"	84.6%	41.1
.072"	.9280"	86.1%	33.3
.063"	.9370"	87.8%	25.5
3/4" x 3/4" MESH			
.250"	.5000"	44.4%	562.3
.225"	.5250"	49.0%	451.0
.207"	.5430"	52.4%	379.4
.192"	.5580"	55.3%	324.8
.177"	.5730"	58.3%	274.7
.162"	.5880"	61.4%	229.2
.148"	.6020"	64.4%	190.5
.135"	.6150"	67.2%	158.1
.120"	.6300"	70.5%	124.4
.105"	.6450"	73.9%	95.0
.092"	.6580"	76.9%	72.8
.080"	.6700"	79.8%	54.9
.072"	.6780"	81.7%	44.5
.063"	.6870"	83.9%	34.0
.054"	.6960"	86.1%	24.9
5/8" x 5/8" MESH			
.250"	.3750"	36.0%	689.4
.225"	.4000"	41.0%	551.0
.207"	.4180"	44.7%	462.4
.192"	.4330"	48.0%	395.0
.177"	.4480"	51.4%	333.5
.162"	.4630"	54.9%	277.7
.148"	.4770"	58.3%	230.5
.135"	.4900"	61.5%	191.0
.120"	.5050"	65.3%	150.2
.105"	.5200"	69.2%	114.5
.092"	.5330"	72.7%	87.9
.080"	.5450"	76.0%	66.1
.072"	.5530"	78.3%	53.5
.063"	.5620"	80.9%	40.9
.054"	.5710"	83.5%	30.0
.047"	.5780"	85.5%	22.7

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
2 x 2 MESH			
.250"	.2500"	25.0%	894.6
.225"	.2750"	30.3%	710.6
.207"	.2930"	34.3%	593.8
.192"	.3080"	37.9%	505.5
.177"	.3230"	41.7%	425.4
.162"	.3380"	45.7%	353.3
.148"	.3520"	49.6%	292.4
.135"	.3650"	53.3%	241.7
.120"	.3800"	57.8%	189.6
.105"	.3950"	62.4%	144.2
.092"	.4080"	66.6%	110.2
.080"	.4200"	70.6%	83.0
.072"	.4280"	73.3%	67.1
.063"	.4370"	76.4%	51.2
.054"	.4460"	79.6%	37.6
.047"	.4530"	81.2%	28.4
.041"	.4590"	84.3%	21.6
.035"	.4650"	86.5%	15.7
2-1/4 x 2-1/4 MESH			
.225"	.2194"	24.4%	817.9
.207"	.2374"	28.4%	680.9
.192"	.2524"	32.2%	578.4
.177"	.2674"	36.1%	485.7
.162"	.2824"	40.3%	402.3
.148"	.2964"	44.4%	332.5
.135"	.3094"	48.3%	274.3
.120"	.3244"	53.1%	214.8
.105"	.3394"	58.2%	163.2
.092"	.3524"	62.7%	124.5
.080"	.3644"	67.1%	93.7
.072"	.3724"	70.1%	75.7
.063"	.3814"	73.5%	57.8
.054"	.3904"	77.0%	42.3
.047"	.3974"	79.8%	32.0
.041"	.0434"	82.2%	24.3
2-1/2 x 2-1/2 MESH			
.225"	.1750"	19.1%	929.3
.207"	.1930"	23.3%	772.2
.192"	.2080"	27.0%	654.4
.177"	.2230"	31.1%	548.2
.162"	.2380"	35.4%	453.4
.148"	.2520"	39.7%	373.7
.135"	.2650"	43.9%	307.8
.120"	.2800"	49.0%	240.6
.105"	.2950"	54.4%	182.4
.092"	.3080"	59.3%	139.0
.080"	.3200"	64.0%	104.4

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
2-1/2 x 2-1/2 MESH CONT.			
.072"	.3280"	67.2%	84.3
.063"	.3370"	71.0%	64.3
.054"	.3460"	74.8%	47.1
.047"	.3530"	77.9%	35.6
.041"	.3590"	80.6%	27.0
.035"	.3650"	83.3%	19.7
2-3/4 x 2-3/4 MESH			
.177"	.1866"	26.3%	613.4
.162"	.2016"	30.7%	505.8
.148"	.2156"	35.2%	416.3
.135"	.2286"	39.5%	342.2
.120"	.2436"	44.9%	267.0
.105"	.2586"	50.6%	202.0
.092"	.2716"	55.8%	153.7
.080"	.2836"	60.8%	115.3
.072"	.2916"	64.3%	93.0
.063"	.3006"	68.3%	70.9
.054"	.3096"	72.5%	51.9
.047"	.3166"	75.8%	39.2
.041"	.3226"	78.7%	29.8
.035"	.3286"	81.7%	21.7
3 x 3 MESH			
.162"	.1713"	26.3%	560.4
.148"	.1853"	30.8%	460.2
.135"	.1983"	35.3%	377.6
.120"	.2133"	40.8%	293.9
.105"	.2283"	46.8%	222.0
.092"	.2413"	52.3%	168.7
.080"	.2533"	57.6%	126.4
.072"	.2613"	61.3%	101.9
.063"	.2703"	65.6%	77.6
.054"	.2793"	70.1%	56.7
.047"	.2863"	73.6%	42.8
.041"	.2923"	76.7%	32.5
.035"	.2983"	79.9%	23.7
.032"	.3013"	81.5%	19.7
3-1/4 x 3-1/4 MESH			
.148"	.1597"	26.9%	505.6
.135"	.1727"	31.5%	414.0
.120"	.1877"	37.2%	321.6
.105"	.2027"	43.4%	242.4
.092"	.2157"	49.1%	183.8
.080"	.2277"	54.8%	137.6
.072"	.2357"	58.7%	110.8
.063"	.2447"	63.2%	84.3
.054"	.2537"	68.0%	61.6
.047"	.2607"	71.8%	46.5



WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
3-1/4 x 3-1/4 MESH CONT.			
.041"	.2667"	75.1%	35.3
.035"	.2727"	78.5%	25.6
.032"	.2757"	80.3%	21.4
3-1/2 x 3-1/2 MESH			
.148"	.1377"	23.2%	525.0
.135"	.1507"	27.9%	429.0
.120"	.1657"	33.8%	349.9
.105"	.1807"	40.1%	263.2
.092"	.1937"	46.1%	199.3
.080"	.2057"	52.0%	148.9
.072"	.2137"	56.1%	119.8
.063"	.2227"	60.9%	91.1
.054"	.2317"	65.9%	66.5
.047"	.2387"	70.0%	50.2
.041"	.2447"	73.5%	38.1
.035"	.2507"	77.2%	27.6
.032"	.2537"	79.0%	23.1
3-3/4 x 3-3/4 MESH			
.148"	.1187"	19.9%	571.3
.135"	.1317"	24.4%	465.9
.120"	.1467"	30.3%	360.1
.105"	.1617"	36.8%	284.5
.092"	.1747"	42.9%	215.0
.080"	.1867"	49.0%	160.4
.072"	.1947"	53.3%	128.9
.063"	.2037"	58.4%	97.9
.054"	.2127"	63.6%	71.4
.047"	.2197"	67.9%	53.8
.041"	.2257"	71.6%	40.8
.035"	.2317"	75.5%	29.7
.032"	.2347"	77.5%	24.8
4 x 4 MESH			
.148"	.1020"	16.6%	619.1
.135"	.1150"	21.2%	503.8
.120"	.1300"	27.0%	388.6
.105"	.1450"	33.6%	306.2
.092"	.1580"	39.9%	231.0
.080"	.1700"	46.2%	172.1
.072"	.1780"	50.7%	138.2
.063"	.1870"	56.0%	104.8
.054"	.1960"	61.5%	76.4
.047"	.2030"	65.9%	57.6
.041"	.2090"	69.9%	43.6
.035"	.2150"	74.0%	31.7
.032"	.2180"	76.0%	26.4
.028"	.2220"	78.9%	20.2
.025"	.2250"	81.0%	16.1

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
4-1/2 x 4-1/2 MESH			
.120"	.1022"	21.2%	447.9
.105"	.1172"	27.7%	333.7
.092"	.1302"	34.2%	26.9
.080"	.1422"	40.8%	195.9
.072"	.1502"	45.6%	157.0
.063"	.1592"	51.2%	118.9
.054"	.1682"	57.2%	86.4
.047"	.1752"	62.0%	65.0
.041"	.1812"	66.3%	49.2
.035"	.1872"	70.8%	35.7
.032"	.1902"	73.1%	29.8
.028"	.1942"	76.4%	22.8
.025"	.1972"	78.7%	18.1
5 x 5 MESH			
.120"	.0800"	16.0%	510.6
.105"	.0950"	22.6%	378.7
.092"	.1080"	29.2%	283.4
.080"	.1200"	36.0%	220.6
.072"	.1280"	41.0%	176.4
.063"	.1370"	46.9%	133.2
.054"	.1460"	53.3%	96.7
.047"	.1530"	58.5%	72.6
.041"	.1590"	63.2%	54.9
.035"	.1650"	68.1%	39.8
.032"	.1680"	70.6%	33.2
.028"	.1720"	74.0%	25.3
.025"	.1750"	76.6%	20.2
.023"	.1770"	78.3%	17.0
5-1/2 x 5-1/2 MESH			
.105"	.0768"	17.9%	448.3
.092"	.0898"	24.4%	317.3
.080"	.1018"	31.3%	233.9
.072"	.1098"	36.5%	196.3
.063"	.1188"	42.7%	147.9
.054"	.1278"	49.4%	107.1
.047"	.1348"	55.0%	80.3
.041"	.1408"	60.0%	60.7
.035"	.1468"	65.2%	43.9
.032"	.1498"	67.9%	36.6
.028"	.1538"	71.6%	27.9
.025"	.1568"	74.4%	22.2
.023"	.1588"	76.3%	18.8
6 x 6 MESH			
.092"	.0747"	20.2%	352.8
.080"	.0867"	27.2%	259.1
.072"	.0947"	32.5%	216.9
.063"	.1037"	38.9%	163.0

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
6 x 6 MESH CONT.			
.054"	.1127"	46.0%	117.7
.047"	.1197"	51.8%	88.2
.041"	.1257"	57.2%	66.5
.035"	.1317"	62.7%	48.1
.032"	.1347"	65.6%	40.0
.028"	.1387"	69.6%	30.5
.025"	.1417"	72.6%	24.3
.023"	.1437"	74.7%	20.5
.020"	.1467"	77.8%	15.5
6-1/2 x 6-1/2 MESH			
.092"	.0619"	16.2%	389.9
.080"	.0739"	23.1%	285.1
.072"	.0819"	28.3%	226.3
.063"	.0909"	34.9%	169.6
.054"	.0999"	42.2%	128.6
.047"	.1069"	48.3%	96.1
.041"	.1129"	53.9%	72.4
.035"	.1189"	59.7%	52.3
.032"	.1219"	62.8%	43.5
.028"	.1259"	67.0%	33.2
.025"	.1289"	70.2%	26.3
.023"	.1309"	72.4%	22.3
.020"	.1339"	75.8%	16.8
7 x 7 MESH			
.080"	.0629"	19.4%	312.2
.072"	.0709"	24.6%	247.2
.063"	.0799"	31.4%	184.7
.054"	.0889"	38.8%	139.7
.047"	.0959"	45.2%	104.2
.041"	.1019"	51.0%	78.4
.035"	.1079"	57.2%	56.5
.032"	.1109"	60.4%	47.0
.028"	.1149"	64.8%	35.8
.025"	.1179"	68.2%	28.4
.023"	.1199"	70.6%	24.0
.020"	.1229"	74.1%	18.1
.018"	.1249"	76.6%	14.6
7-1/2 x 7-1/2 MESH			
.080"	.0533"	16.0%	317.48
.072"	.0613"	21.1%	257.16
.063"	.0703"	27.8%	200.3
.054"	.0793"	35.4%	151.0
.047"	.0863"	41.9%	112.5
.041"	.0923"	47.9%	84.4
.035"	.0983"	54.4%	60.8
.032"	.1013"	57.7%	50.6
.028"	.1053"	62.4%	38.4



WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
7-1/2 x 7-1/2 MESH CONT.			
.025"	.1083"	66.0%	30.5
.023"	.1103"	68.4%	25.8
.020"	.1133"	72.2%	19.4
.018"	.1153"	74.8%	15.7
8 x 8 MESH			
.072"	.0530"	18.0%	291.1
.063"	.0620"	24.6%	216.3
.054"	.0710"	32.3%	162.7
.047"	.0780"	38.9%	120.9
.041"	.0840"	45.2%	90.6
.035"	.0900"	51.8%	65.1
.032"	.0930"	55.4%	54.1
.028"	.0970"	60.2%	41.1
.025"	.1000"	64.0%	32.6
.023"	.1020"	66.6%	27.5
.020"	.1050"	70.6%	20.7
.018"	.1070"	73.3%	16.8
.017"	.1080"	74.6%	14.9
8-1/2 x 8-1/2 MESH			
.072"	.0456"	15.0%	314.3
.063"	.0546"	21.5%	232.8
.054"	.0636"	29.2%	165.9
.047"	.0706"	36.0%	129.4
.041"	.0766"	42.4%	96.8
.035"	.0826"	49.3%	69.5
.032"	.0856"	52.9%	57.7
.028"	.0896"	58.0%	43.8
.025"	.0926"	62.0%	34.8
.023"	.0946"	64.7%	29.3
.020"	.0976"	68.8%	22.1
.018"	.0996"	71.7%	17.8
.017"	.1006"	73.1%	15.9
9 x 9 MESH			
.072"	.0391"	12.4%	338.2
.063"	.0481"	18.7%	249.8
.054"	.0571"	26.3%	177.4
.047"	.0641"	33.2%	138.2
.041"	.0701"	39.7%	103.2
.035"	.0761"	46.8%	74.0
.032"	.0791"	50.6%	61.4
.028"	.0831"	55.8%	46.6
.025"	.0861"	59.9%	36.9
.023"	.0881"	62.7%	31.1
.020"	.0911"	67.1%	23.4
.018"	.0931"	70.1%	18.9
.017"	.0941"	71.6%	16.8
.016"	.0951"	73.1%	14.9

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
9-1/2 x 9-1/2 MESH			
.063"	.0423"	16.1%	267.3
.054"	.0513"	23.8%	189.3
.047"	.0583"	30.7%	147.1
.041"	.0643"	37.3%	109.7
.035"	.0703"	44.6%	78.5
.032"	.0733"	48.5%	65.1
.028"	.0773"	53.9%	49.3
.025"	.0803"	58.2%	39.1
.023"	.0823"	61.1%	32.9
.020"	.0853"	65.7%	24.8
.018"	.0873"	68.8%	20.0
.017"	.0883"	70.4%	17.8
.016"	.0893"	72.0%	15.7
10 x 10 MESH			
.063"	.0370"	13.7%	285.4
.054"	.0460"	21.2%	201.5
.047"	.0530"	28.1%	148.4
.041"	.0590"	34.8%	116.3
.035"	.0650"	42.3%	83.1
.032"	.0680"	46.2%	68.8
.028"	.0720"	51.8%	52.1
.025"	.0750"	56.3%	41.2
.023"	.0770"	59.3%	34.7
.020"	.0800"	64.0%	26.1
.018"	.0820"	67.2%	21.1
.017"	.0830"	68.9%	18.8
.016"	.0840"	70.6%	16.6
.015"	.0850"	72.3%	14.6
11 x 11 MESH			
.054"	.0369"	16.6%	226.9
.047"	.0439"	23.3%	166.3
.041"	.0499"	30.1%	123.3
.035"	.0559"	37.8%	92.4
.032"	.0589"	42.0%	76.4
.028"	.0629"	47.9%	57.8
.025"	.0659"	52.5%	45.6
.023"	.0679"	55.8%	38.4
.020"	.0709"	60.8%	28.8
.018"	.0729"	64.3%	23.3
.017"	.0739"	66.1%	20.7
.016"	.0749"	67.9%	18.3
.015"	.0759"	69.7%	16.1
12 x 12 MESH			
.047"	.0363"	18.7%	185.1
.041"	.0423"	25.4%	136.7
.035"	.0483"	33.2%	102.1
.032"	.0513"	37.5%	84.3

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
12 x 12 MESH CONT.			
.028"	.0553"	43.6%	63.5
.025"	.0583"	48.4%	50.1
.023"	.0603"	51.8%	42.2
.020"	.0633"	57.2%	31.6
.018"	.0653"	60.8%	25.5
.017"	.0663"	62.7%	22.7
.016"	.0673"	64.5%	20.0
.015"	.0683"	66.6%	17.6
.014"	.0693"	68.6%	15.3
13 x 13 MESH			
.041"	.0359"	21.8%	150.6
.035"	.0419"	29.7%	106.4
.032"	.0449"	34.1%	92.3
.028"	.0489"	40.4%	69.4
.025"	.0519"	45.5%	54.7
.023"	.0539"	49.1%	45.9
.020"	.0569"	54.7%	34.4
.018"	.0589"	58.6%	27.7
.017"	.0599"	60.6%	24.6
.016"	.0609"	62.7%	21.8
.015"	.0619"	64.8%	19.1
.014"	.0629"	66.9%	16.6
14 x 14 MESH			
.041"	.0304"	17.6%	165.0
.035"	.0364"	25.4%	116.1
.032"	.0394"	29.8%	100.5
.028"	.0434"	36.2%	75.5
.025"	.0464"	41.5%	59.3
.023"	.0484"	45.2%	49.8
.020"	.0514"	51.0%	37.2
.018"	.0534"	55.1%	29.9
.017"	.0544"	57.2%	26.6
.016"	.0554"	59.3%	23.5
.015"	.0564"	61.5%	20.6
.014"	.0574"	63.7%	17.9
.0135"	.0575"	64.8%	16.6
.013"	.0584"	65.9%	15.4
.012"	.0594"	68.2%	13.1
.011"	.0604"	70.6%	11.0
.010"	.0614"	72.9%	9.0
15 x 15 MESH			
.041"	.0257"	15.2%	180.0
.035"	.0317"	22.6%	126.2
.032"	.0347"	27.1%	103.6
.028"	.0387"	33.7%	77.6
.025"	.0417"	39.1%	64.1
.023"	.0437"	43.0%	53.7



WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
15 x 15 MESH CONT.			
.020"	.0467"	49.1%	40.1
.018"	.0487"	53.4%	32.2
.017"	.0497"	55.8%	28.6
.016"	.0507"	57.8%	25.3
.015"	.0517"	60.1%	22.1
.014"	.0527"	62.5%	19.2
.0135"	.0532"	63.7%	17.9
.013"	.0537"	64.9%	16.5
.012"	.0547"	67.3%	14.1
.011"	.0557"	69.8%	11.8
.010"	.0567"	72.3%	9.7
16 x 16 MESH			
.035"	.0275"	19.4%	136.6
.032"	.0305"	23.8%	111.9
.028"	.0345"	30.5%	83.6
.025"	.0375"	36.0%	68.9
.023"	.0395"	39.9%	57.7
.020"	.0425"	46.2%	43.0
.018"	.0445"	50.7%	34.5
.017"	.0455"	53.0%	30.7
.016"	.0465"	55.4%	27.1
.015"	.0475"	57.8%	23.7
.014"	.0485"	60.2%	20.6
.0135"	.0490"	61.5%	19.1
.013"	.0495"	62.7%	17.7
.012"	.0505"	65.3%	15.0
.011"	.0515"	67.9%	12.6
.010"	.0525"	70.6%	10.4
.0095"	.0530"	71.9%	9.4
18 x 18 MESH			
.035"	.0206"	13.7%	158.4
.032"	.0236"	18.0%	129.4
.028"	.0276"	24.7%	96.1
.025"	.0306"	30.3%	75.0
.023"	.0326"	34.4%	66.0
.020"	.0356"	41.1%	49.0
.018"	.0376"	45.8%	39.2
.017"	.0386"	48.3%	34.8
.016"	.0396"	50.8%	30.7
.015"	.0406"	53.4%	26.8
.014"	.0416"	56.1%	23.3
.0135"	.0421"	57.4%	21.6
.013"	.0426"	58.8%	20.0
.012"	.0436"	61.6%	17.0
.011"	.0446"	64.4%	14.2
.010"	.0456"	67.4%	11.7
.0095"	.0460"	68.9%	10.5
.009"	.0466"	70.4%	9.5

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
20 x 20 MESH			
.032"	.0180"	13.0%	147.9
.028"	.0220"	19.4%	109.3
.025"	.0250"	25.0%	85.0
.023"	.0270"	29.2%	70.8
.020"	.0300"	36.0%	55.2
.018"	.0320"	41.0%	44.1
.017"	.0330"	43.6%	39.1
.016"	.0340"	46.2%	34.4
.015"	.0350"	49.0%	30.1
.014"	.0360"	51.8%	26.1
.0135"	.0370"	53.3%	24.2
.013"	.0370"	54.8%	22.4
.012"	.0380"	57.8%	19.0
.011"	.0390"	60.8%	15.9
.010"	.0400"	64.0%	13.1
.0095"	.0405"	65.6%	11.8
.009"	.0410"	67.2%	10.5
22 x 22 MESH			
.028"	.0175"	14.8%	123.2
.025"	.0205"	20.3%	95.4
.023"	.0225"	24.5%	79.3
.020"	.0255"	31.5%	58.5
.018"	.0275"	36.6%	49.1
.017"	.0285"	39.3%	43.5
.016"	.0295"	42.1%	38.2
.015"	.0305"	45.0%	33.4
.014"	.0315"	48.0%	28.9
.0135"	.0320"	49.6%	26.8
.013"	.0325"	51.1%	24.8
.012"	.0335"	54.3%	21.0
.011"	.0345"	57.6%	17.5
.010"	.0355"	61.0%	14.4
.0095"	.0360"	62.7%	13.0
.009"	.0365"	64.5%	11.6
24 x 24 MESH			
.025"	.0167"	16.1%	106.4
.023"	.0187"	20.1%	88.2
.020"	.0217"	27.1%	64.8
.018"	.0237"	32.4%	51.5
.017"	.0247"	35.1%	48.0
.016"	.0257"	38.0%	42.1
.015"	.0267"	41.1%	36.7
.014"	.0277"	44.2%	31.8
.0135"	.0282"	45.8%	29.4
.013"	.0287"	47.4%	27.2
.012"	.0297"	50.8%	23.0
.011"	.0307"	54.3%	19.2
.010"	.0317"	57.9%	15.8

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
24 x 24 MESH CONT.			
.0095"	.0322"	59.7%	14.2
.009"	.0327"	61.6%	12.7
.0085"	.0332"	63.5%	11.3
.008"	.0337"	65.4%	10.0
.0075"	.0342"	67.4%	8.8
26 x 26 MESH			
.020"	.0185"	23.1%	71.3
.018"	.0205"	28.4%	56.6
.017"	.0215"	31.2%	52.6
.016"	.0225"	34.2%	46.1
.015"	.0235"	37.3%	40.2
.014"	.0245"	40.6%	34.7
.0135"	.0250"	42.3%	32.1
.013"	.0255"	44.0%	29.7
.012"	.0265"	47.5%	25.1
.011"	.0275"	51.1%	20.9
.010"	.0285"	54.9%	17.2
.0095"	.0290"	56.9%	15.5
.009"	.0295"	58.8%	13.8
.0085"	.0300"	60.8%	12.3
.008"	.0305"	62.9%	10.9
.0075"	.0310"	65.0%	9.5
28 x 28 MESH			
.018"	.0177"	24.6%	61.8
.017"	.0187"	27.4%	54.5
.016"	.0197"	30.4%	50.3
.015"	.0207"	33.9%	43.7
.014"	.0217"	36.9%	37.7
.0135"	.0222"	38.6%	34.9
.013"	.0227"	40.4%	32.2
.012"	.0237"	44.0%	27.2
.011"	.0247"	47.8%	22.7
.010"	.0257"	51.8%	18.6
.0095"	.0262"	53.8%	16.7
.009"	.0267"	55.9%	15.0
.0085"	.0272"	58.0%	13.3
.008"	.0277"	60.2%	11.8
.0075"	.0282"	62.3%	10.3
30 x 30 MESH			
.017"	.0163"	23.9%	59.2
.016"	.0173"	26.9%	61.8
.015"	.0183"	30.1%	47.4
.014"	.0193"	33.5%	40.8
.0135"	.0198"	35.3%	37.8
.013"	.0203"	37.1%	34.8
.012"	.0213"	40.8%	29.4
.011"	.0223"	44.8%	24.5
.010"	.0233"	48.9%	20.0

Superior Service, Quality and Performance ... That's The Hole Story®!



WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
30 x 30 MESH CONT.			
.0095"	.0238"	51.0%	18.0
.009"	.0243"	53.1%	16.1
.0085"	.0248"	55.4%	14.3
.008"	.0253"	57.6%	12.6
.0075"	.0258"	59.9%	11.1
.0065"	.0266"	64.8%	8.4
32 x 32 MESH			
.016"	.0153"	24.0%	56.0
.015"	.0163"	27.2%	48.6
.014"	.0173"	30.6%	44.0
.0135"	.0178"	32.4%	40.7
.013"	.0183"	34.3%	37.5
.012"	.0193"	38.1%	31.6
.011"	.0203"	42.2%	26.3
.010"	.0213"	46.5%	21.5
.0095"	.0218"	48.7%	19.3
.009"	.0223"	50.9%	17.3
.0085"	.0228"	53.2%	15.3
.008"	.0233"	55.6%	13.5
.0075"	.0238"	58.0%	11.8
.007"	.0243"	60.5%	10.3
35 x 35 MESH			
.016"	.0126"	19.4%	62.4
.015"	.0136"	22.7%	54.1
.014"	.0146"	26.1%	46.5
.0135"	.0151"	27.9%	45.2
.013"	.0156"	29.8%	41.6
.012"	.0166"	33.8%	35.0
.011"	.0176"	37.9%	29.0
.010"	.0186"	42.4%	23.7
.0095"	.0191"	44.7%	21.3
.009"	.0196"	47.1%	19.0
.0085"	.0201"	49.5%	16.9
.008"	.0206"	52.0%	14.9
.0075"	.0211"	54.5%	13.0
.007"	.0216"	57.2%	11.3
38 x 38 MESH			
.014"	.0123"	21.8%	51.3
.0135"	.0128"	24.7%	47.3
.013"	.0133"	25.5%	43.6
.012"	.0143"	29.5%	38.5
.011"	.0153"	33.8%	31.9
.010"	.0163"	38.4%	26.0
.0095"	.0168"	40.8%	23.3
.009"	.0173"	43.2%	20.8
.0085"	.0178"	45.8%	18.5
.008"	.0183"	48.4%	16.3
.0075"	.0188"	51.0%	14.2

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
38 x 38 MESH CONT.			
.007"	.0193"	53.8%	12.3
40 x 40 MESH			
.0135"	.0115"	21.2%	53.0
.013"	.0120"	23.0%	48.8
.012"	.0130"	27.0%	40.9
.011"	.0140"	31.4%	33.8
.010"	.0150"	36.0%	27.6
.0095"	.0155"	38.4%	24.7
.009"	.0160"	41.0%	22.0
.0085"	.0165"	43.6%	19.5
.008"	.0170"	46.2%	17.2
.0075"	.0175"	49.0%	15.0
.007"	.0180"	51.8%	13.0
.0065"	.0185"	54.8%	11.3
42 x 42 MESH			
.0135"	.0103"	18.7%	53.5
.013"	.0108"	20.6%	51.8
.012"	.0118"	24.6%	43.4
.011"	.0128"	28.9%	35.8
.010"	.0138"	33.6%	29.2
.0095"	.0143"	36.1%	26.1
.009"	.0148"	38.6%	23.3
45 x 45 MESH			
.013"	.0092"	17.1%	53.6
.012"	.0102"	21.1%	44.8
.011"	.0112"	25.4%	36.9
.010"	.0122"	30.1%	31.6
.0095"	.0127"	32.7%	28.3
.009"	.0132"	35.3%	25.2
.0085"	.0137"	38.0%	22.3
.008"	.0142"	40.8%	19.6
.0075"	.0147"	43.8%	17.1
50 x 50 MESH			
.012"	.0080"	16.0%	51.1
.011"	.0090"	20.3%	42.0
.010"	.0100"	25.0%	34.0
.0095"	.0105"	27.6%	32.0
.009"	.0110"	30.3%	28.4
.0085"	.0115"	33.1%	25.1
.008"	.0120"	36.0%	22.1
.0075"	.0125"	39.1%	19.2
.0065"	.0135"	44.3%	14.4
55 x 55 MESH			
.011"	.0072"	15.7%	47.3
.010"	.0082"	20.3%	38.2
.0095"	.0087"	22.9%	34.0
.009"	.0092"	25.6%	30.2
.0085"	.0097"	28.5%	28.1

WIRE DIAMETER	OPENING SIZE	PERCENT OPEN AREA	100 #/SF
55 x 55 MESH CONT.			
.008"	.0102"	31.5%	24.6
.0075"	.0107"	34.6%	21.4
.007"	.0112"	37.9%	18.5
60 x 60 MESH			
.011"	.0057"	11.7%	52.9
.010"	.0067"	16.2%	42.6
.0095"	.0072"	18.7%	37.9
.009"	.0077"	21.3%	33.5
.0085"	.0082"	24.2%	29.6
.008"	.0087"	27.2%	27.3
.0075"	.0092"	30.5%	23.7
.007"	.0097"	33.9%	20.4
.0065"	.0102"	37.5%	17.4
.006"	.0107"	41.2%	14.7
65 x 65 MESH			
.0075"	.0079"	26.4%	26.0
.007"	.0084"	29.8%	22.4
.0065"	.0089"	33.5%	19.1
70 x 70 MESH			
.009"	.0053"	13.8%	40.7
.0085"	.0058"	16.5%	35.8
.008"	.0063"	19.4%	31.3
.0075"	.0068"	22.7%	27.1
.007"	.0073"	26.1%	23.3
.0065"	.0078"	29.8%	20.8
.006"	.0083"	33.8%	17.5
75 x 75 MESH			
.007"	.0063"	22.3%	25.3
.0065"	.0068"	26.0%	22.6
.006"	.0073"	30.0%	19.0
80 x 80 MESH			
.0075"	.0050"	16.0%	31.9
.007"	.0055"	19.4%	27.4
.0065"	.0060"	23.0%	23.2
.006"	.0065"	27.0%	20.4
.0055"	.0070"	31.4%	16.9
.005"	.0075"	36.0%	13.8
90 x 90 MESH			
.006"	.0051"	21.1%	22.4
.0055"	.0056"	25.4%	18.4
.005"	.0061"	30.1%	15.8
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

Superior Service, Quality and Performance ... That's The Hole Story®!

